

Temperature & Model Dip-Switch Settings for REU V2626WG ONLY



- Confirm that **ALL DIGITS** of the model number on the appliance dataplate match one of the model numbers above (*including the letters G, B, E & S in the Model Number*).
- Water heaters that have "(50)" in the model number or nominated on the front panel of the water heater cannot be adjusted to temperatures above 50°C.



- Dipswitch settings must only be set by an authorised person.
- All dipswitches **MUST** be set for the particular model in accordance with this Instruction. Incorrect dipswitch settings may result in a dangerous condition or damage to the appliance.
- It is the responsibility of the authorised person changing the dipswitch settings to ensure the installation complies with the requirements of AS/NZS 3500.4 and any local regulations regarding water delivery temperature to areas primarily used for personal hygiene (50°C).

<p>Propane</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>40°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>	<p>Natural</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>40°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>
<p>Propane</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>42°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>	<p>Natural</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>42°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>
<p>Propane</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>50°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>	<p>Natural</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>50°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>
<p>Propane</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>55°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>	<p>Natural</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>55°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>
<p>Propane</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>60°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>	<p>Natural</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>60°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>
<p>Propane</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>65°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>	<p>Natural</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>65°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>
<p>Propane</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>75°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>	<p>Natural</p> <p>Off On SW 1</p> <p>1 2 3 4 5 6 7 8</p> <p>Model Type</p> <p>75°C</p> <p>Gas Pressures</p> <p>Off On SW 2</p> <p>1 2 3 4</p> <p>Gas Type</p> <p>Model Type</p>
<p style="text-align: center;">Legend</p> <p>Off On SW 1</p> <p>Black indicates position of switch</p> <p>Notes:</p> <ol style="list-style-type: none"> Solar water heaters S20 & S26 are Rinnai Japan factory preset to 60°C. These settings must not be altered. Temperature dipswitches do not operate on Rinnai Japan factory preset 50°C models, - (50) in product model code. 85°C is not available on this model. 	