

Temperature & Model Dip-Switch Settings for Enviro 32 (Temp Adjustable) - REU KM3237WD ONLY



- Confirm that ALL DIGITS of the model number on the appliance dataplate match the model numbers above.



- Dipswitch settings must only be set by an authorised person.
- All dipswitches MUST be set for the particular model in accordance with this Instruction. Incorrect dipswitch settings may result in a dangerous condition or damage to the appliance.

Dipswitch Settings

Dip Switches Explained & Model Setting

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

Model Type Factory Set

Temperatures

Gas Pressures

Off	On	SW 2
		1
		2
		3
		4

Gas Type

Model Type

Gas Type

Off	On	SW 2
		1
		2
		3
		4

Nat Gas

Off	On	SW 2
		1
		2
		3
		4

Propane Gas

Gas Pressures

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

Normal Combustion

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

Forced low Combustion

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

Note: After setting gas pressures return both 7 and 8 dipswitches to the OFF position for normal combustion.

Forced High Combustion

Model Type

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

REU-KM3237WD (Enviro 32)

Off	On	SW 2
		1
		2
		3
		4

Temperature

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

40°C
As from 1st May 2010, Rinnai cannot provide this dipswitch setting to customers. Contact TSD for further Information

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

42°C
As from 1st May 2010, Rinnai cannot provide this dipswitch setting to customers. Contact TSD for further Information

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

50°C
As from 1st May 2010, Rinnai cannot provide this dipswitch setting to customers. Contact TSD for further Information

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

55°C

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

60°C

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

65°C

Off	On	SW 1
		1
		2
		3
		4
		5
		6
		7
		8

75°C

Legend

Off	On

Black indicates position of switch